

# Product datasheet

Specifications

**CLIPSAL**



## Master Mechanism, C-Bus Control and Management System, Aperture Grid Plates and Enclosure

5031NMML

### Main

Range	C-Bus
Product brand	Clipsal
product name	Series 30M
Product or component type	Push-button interface
Device application	Control
Colour	White
Switch application	Load switching Dimming up/down control Timer Scene control Bell switch Shutter control Fan speed control Blind control

### Complementary

Range compatibility	C-Bus
Dimmer control	255 possible levels
Device mounting	Wall mounted by Series 30M grid
[Ue] rated operational voltage	15...36 V DC
Input impedance	100 kOhm at 1 kHz
Local signalling	LED (blue/orange) for status
suitable cable type	Twisted unshielded pairs cable category 5e
Isolation voltage	3.75 kV from C-Bus to mains
Communication network type	C-Bus
module type	Master
Control type	Push-button
Depth	41 mm
Width	23 mm
Height	23 mm
Product weight	0.013 kg
Material	Plastic
Starting time	5 s
Module configuration	Programmed with learn mode Programmed with C-Bus software

---

<b>Time delay range</b>	1s...18h12m15s
-------------------------	----------------

---

<b>Current consumption</b>	18 mA
----------------------------	-------

---

## Environment

---

<b>Ambient air temperature for operation</b>	0...45 °C
--	-----------

---

<b>Relative humidity</b>	10...95 % non-condensing
--------------------------	--------------------------

---

<b>Product certifications</b>	RCM
-------------------------------	-----

---

<b>Standards</b>	AS/NZS CISPR 15 AS/NZS CISPR 14-1 AS/NZS 60669.2.1
------------------	--

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	6 cm
-------------------------	------

---

<b>Package 1 Width</b>	3 cm
------------------------	------

---

<b>Package 1 Length</b>	10 cm
-------------------------	-------

---

<b>Package 1 Weight</b>	52 g
-------------------------	------

---

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 2

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Recycled metal content at CR level 0

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

China RoHS Regulation [China RoHS declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No