Specifications

CLIPSAL



Din-Mount Power Supply & Serial Interface, DALIcontrol Lighting Control System, Two Dali lines

DCDALCIP250-2

Main

Range	DALI Control	
Product brand	Clipsal	
Product or component type	Dual power supply and serial interface	
Device application	Communication Power supply	

Complementary

· ·		
Number output current	<= 235 mA	
[Us] rated supply voltage	110 V AC 50 Hz	
	240 V AC 60 Hz	
Output current	<= 235 mA line	
Supply circuit type	AC	
number of lines feed	2	
Number of modules	4	
Local signalling	LED	
Mounting support	DIN rail	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.6 cm
Package 1 Width	7.8 cm
Package 1 Length	9.6 cm
Package 1 Weight	208.0 g

🜔 Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

3

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)

Use Better

Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

Use Again

${igvarrightarrow}$ Repack and remanufacture	
Take-back	No