

SpaceLogic Wall Plate, C-Bus, Saturn, A-Series, Key Input unit, 2 keys

5082PW

Main

| Product brand | Schneider Electric | |
|---------------------------|-----------------------|--|
| Range | SpaceLogic C-Bus | |
| product name | C-Bus Saturn A Series | |
| Product or component type | Switch | |
| Device application | Control | |
| Colour tint | Pure white | |

Complementary

| Device presentation | Complete product | |
|--------------------------------|--|--|
| Number of gangs | 2 gangs | |
| Control type | Push-button | |
| Provided equipment | fascia plate | |
| | body switch push-button cap | |
| Material | Glass | |
| [Ue] rated operational voltage | 1536 V DC | |
| [In] rated current | 22 mA | |
| Communication network type | C-Bus | |
| Input impedance | 50 kOhm at 1 kHz | |
| Isolation voltage | 3.75 kV from C-Bus to mains | |
| Switch function | Load switching Dimmer | |
| | | |
| | Time switch function Scene control | |
| | | |
| | Roller shutter | |
| | Bell push switch Curtain | |
| | Roller blind | |
| | Toggle | |
| | roggie | |
| Local signalling | LED (red, green and blue) for status | |
| Connections - terminals | Terminal block - 0.21.3 mm² (AWG 24AWG 16) | |
| Mounting support | Wall-mount | |
| fixing center | 84 mm | |
| Width | 75 mm | |
| Height | 116 mm | |
| Depth | 28 mm | |
| | | |

| Product weight | 54 g |
|------------------|------------|
| Main colour tint | Pure white |

Environment

| Ambient air temperature for operation | 045 °C | |
|---------------------------------------|-----------------------|--|
| Relative humidity | 1095 % non-condensing | |
| Product certifications | RCM CE UKCA | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|--------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 12 cm |
| Package 1 Width | 75 cm |
| Package 1 Length | 16 cm |
| Package 1 Weight | 234 g |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 16 cm |
| Package 2 Width | 225 cm |
| Package 2 Length | 345 cm |
| Package 2 Weight | 2.7 kg |



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

| ∅ Environmental footprint | |
|---|-------------------------------|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 80 |
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Materials and Substances | |
|--|------------------------|
| Recycled metal content at CR level | 0 |
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| China RoHS Regulation | China RoHS declaration |

Use Again

| ○ Repack and remanufacture | |
|----------------------------|-------------------------|
| Circularity Profile | End of Life Information |
| Take-back | No |