

Product datasheet

Specifications

CLIPSAL



PC Interface, C-Bus Control and Management System, Housed in A 4M, Din Rail Enclosure, USB

5500PCU

Main

Range	C-Bus
Product brand	Clipsal
Product or component type	Interface module
Device application	Connection

Complementary

Number of modules	4
communication port protocol	USB
Communication port support	USB
Transmission rate	9600 bauds
Mounting support	DIN rail
Local signalling	LED

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.2 cm
Package 1 Width	12.7 cm
Package 1 Length	16.5 cm
Package 1 Weight	286.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	22.0 cm
Package 2 Width	30.0 cm
Package 2 Length	43.5 cm
Package 2 Weight	3.285 kg
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	80.0 cm

Package 3 Width	120.0 cm
Package 3 Length	110.0 cm
Package 3 Weight	87.84 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **238**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Recycled metal content at CR level **0**

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

China RoHS Regulation [China RoHS declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back **No**