


Product datasheet

Specifications

CLIPSA



Power Supply, C-Bus Control and Management System, DIN Rail Mounted, 250V, 350mA

5500PS

Main

Range	C-Bus
Product brand	Clipsal
Product or component type	Power supply
Device application	Power supply

Complementary

Secondary voltage	32...39 V DC
Number output current	<= 350 mA
[Us] rated supply voltage	240 V AC 50 Hz
Supply circuit type	AC
number of lines feed	1
Number of modules	4
Local signalling	LED

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.77 cm
Package 1 Width	11.164 cm
Package 1 Length	15.586 cm
Package 1 Weight	290.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	23.1 cm
Package 2 Width	24.6 cm
Package 2 Length	34.5 cm
Package 2 Weight	2.941 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **238**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Recycled metal content at CR level **0**

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

China RoHS Regulation [China RoHS declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back **No**