

Relay, C-Bus, DIN Rail Mounted, Voltage Free, 240V AC, 4 Channel, 20A, With C-Bus Power Supply

L5504RVF20

Main

Range of product	C-Bus
Product brand	Clipsal
Range	C-Bus
Product or component type	Relay
Device application	Switching loads

Complementary

Connector type	Screw terminals	
Load type	LED lamp: Incandescent lamps: Fluorescent lamps: Inductive: Motor:	
Inrush current	600 A during 0.15 ms 535 A during 0.19 ms 510 A during 0.21 ms 480 A during 0.23 ms 405 A during 0.33 ms 375 A during 0.4 ms 300 A during 0.6 ms	
[Us] rated supply voltage	1536 V DC	
Device composition	Socket-outlet	
Width	215 mm	
Height	85 mm	
Depth	65 mm	
Number of contacts as normally open contact	4	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.5 cm
Package 1 Width	10.5 cm
Package 1 Length	22 cm
Package 1 Weight	631 g
Unit Type of Package 2	CAR
Number of Units in Package 2	6

Package 2 Height	24.5 cm
Package 2 Width	21 cm
Package 2 Length	34 cm
Package 2 Weight	4.063 kg
Unit Type of Package 3	P12
Number of Units in Package 3	180
Package 3 Height	95 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	130.89 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No